VERSION WITH MARKINGS TO SHOW CHANGES MADE

In the Claims:

Claim 1 has been amended as follows:

1. A personal gas supply delivery system comprising:

a moisturizing vessel, for when in use, having the capability to contain a liquid to provide a source of moisture to increase the amount of moisture in a gas passing through the liquid,

said moisturizing vessel having a first opening for receiving an influent gas,

said moisturizing vessel having a second opening for an effluent gas,

a first conduit connected with said second opening, said first conduit for when in use, for receiving the effluent gas,

a gas flow alarm connected with said first conduit, and

a second conduit connected with said gas flow alarm, said second conduit in fluid communication with said first conduit,

said gas flow alarm for determining the instantaneous pressure or flow volume [differential] of the influent gas and the effluent gas;

said second conduit has a length such that the gas flow alarm, when is use by a recipient of the effluent gas, is proximate to the recipient of the effluent gas.

Cancel Claim 2 without prejudice.

Claim 3 has been amended as follows:

3. The personal gas supply delivery system according to claim 1 wherein the gas flow alarm is set to alert a subject desiring to receive the effluent gas when the pressure [differential] of the influent gas and the effluent gas has met at least one predetermined setting.

Claim 5 has been amended as follows:

5. The personal gas supply delivery system according to claim 1 wherein the gas flow alarm is set to alert a subject desiring to receive the effluent gas when the pressure [differential] of the influent gas and the effluent gas has met at least one predetermined setting and the alerting of the subject is by visible light.

Claim 6 has been amended as follows:

6. The personal gas supply delivery system according to claim 1 wherein the gas

flow alarm is set to alert a subject desiring to receive the effluent gas when the pressure [differential] of the influent gas and the effluent gas has met at least one predetermined setting and the alerting of the subject is audible.

Claim 11 has been amended as follows:

11. A personal gas supply delivery system comprising:

a moisturizing vessel, for when in use, having the capability to contain a liquid to provide a source of moisture to increase the amount of moisture in a gas passing through the liquid,

said moisturizing vessel having a first opening for receiving an influent gas,

said moisturizing vessel having a second opening for an effluent gas,

a first conduit connected with said second opening, said first conduit for when in use, for receiving the effluent gas,

a gas flow alarm connected with said first conduit, and

a second conduit connected with said gas flow alarm, said second conduit in fluid communication with said first conduit,

said second conduit is unitary and connecting with a binary nasal cannula;

said gas flow alarm for determining an instantaneous difference in the pressure or volume of the influent gas per unit of time and the volume of the effluent gas per unit of time.

Cancel Claim 12 without prejudice.

Claim 15 has been amended as follows:

15. The personal gas supply delivery system according to claim 11 wherein the gas flow alarm is set to alert a subject desiring to receive the effluent gas when the volume [differential] of the influent gas and the effluent gas has met at least one predetermined setting and the alerting of the subject is by visible light.

Claim 16 has been amended as follows:

16. The personal gas supply delivery system according to claim 11 wherein the gas flow alarm is set to alert a subject desiring to receive the effluent gas when the volume [differential] of the influent gas and the effluent gas has met at least one predetermined

setting and the alerting of the subject is audible.

Claim 19 has been amended as follows:

19. The personal gas supply delivery system according to claim 18 wherein the gas flow alarm is set to alert a second person by means of a transmitter and a receiver that the pressure [differential] or the volume [differential] per unit of time of the influent gas and the effluent gas has met at least one predetermined setting.

Claim 21 has been amended as follows: CAREFUL ON MARKINGS TO CLAIMS

Claim 21 (Twice Amended) A personal gas supply delivery alarm system comprising:

a first conduit, for when in use receiving a supply of a gas at a first pressure

from a first gas supply line,

said first conduit connected with a battery powered gas flow alarm, said gas flow alarm for when in use

for determining an instantaneous difference in the pressure or volume of the gas per unit of time and the volume of the [effluent] gas per unit of time,

a second conduit connected with said gas flow alarm, for when

in use receiving the supply of gas through said gas flow alarm,

said first conduit having a first connector, for when in use providing a detachable airtight seal with a compatible connector on the gas supply line, said first connector located distally from said gas flow alarm, and

said second conduit having a second connector, for when in use providing a detachable airtight seal with a compatible connector on a second gas supply line, said second connector located distally from said gas flow alarm,

said second gas supply line terminating in a nasal cannula.